

ADO3316PA






FEATURES

- Surface mountable device.
- Low Profile.
- Excellent performance & cost effective.
- Tape & Reel for auto-placement.
- Applicable for DC-DC converter.

BENEFITS

Frequency Range: 0.1 ~ 10 MHz
 Inductance Range: 1.0 ~ 1000 μ H
 Tested: 100 KHz and 0.05V
 Operating Temperature Range: -40°C to +85°C
 Inductance: measured by HP 4194A, impedance and gain phase analyzer.
 Inductance Drop: 10% at rated current

UNIT DIMENSION (unit: mm)




tolerance : ± 0.2

STANDARD SPECIFICATIONS

PACKAGE TYPE	INDUCTANCE (μ H $\pm 20\%$)	DC RESISTANCE (Ω) max.	RATED CURRENT (A) max.
ADO3316PA-102 □	1.0	0.009	9.0
ADO3316PA-152 □	1.5	0.010	8.0
ADO3316PA-222 □	2.2	0.012	7.0
ADO3316PA-332 □	3.3	0.015	6.0
ADO3316PA-472 □	4.7	0.018	4.9
ADO3316PA-682 □	6.8	0.027	4.1
ADO3316PA-103 □	10	0.038	3.3
ADO3316PA-153 □	15	0.046	2.7
ADO3316PA-223 □	22	0.085	2.3
ADO3316PA-333 □	33	0.100	1.8
ADO3316PA-473 □	47	0.140	1.6
ADO3316PA-683 □	68	0.200	1.3
ADO3316PA-104 □	100	0.280	1.10
ADO3316PA-154 □	150	0.400	0.90
ADO3316PA-224 □	220	0.610	0.70
ADO3316PA-334 □	330	1.020	0.60
ADO3316PA-474 □	470	1.270	0.45
ADO3316PA-684 □	680	2.020	0.40
ADO3316PA-105 □	1000	3.000	0.30

Tape & Reel Specifications



XTAL

OSC

VCXO
VCO

TCXO
VCTCXO

FLTR

RES

IND

SPECIFICATIONS

PACKAGE TYPE	A	B	C	D	E	F	G	H	I	J	QTY/REEL
ADO2060A	16.4	330	330	16	3.2	4	8	200	12000	400	2700
ADO1608CA	16.4	60	330	16	3	4	8	200	20000	400	2000
ADT1608CA	16.4	60	330	16	3	4	8	200	20000	400	2000
ADS1608CA	16.4	60	330	16	3	4	8	200	20000	400	2000
ADO3308PA	24.4	100	330	24	3.2	4	12	200	1800	400	1500
ADO3316PA	24.4	100	330	24	5	4	12	200	12000	400	1000
ADS3316PA	24.4	100	330	24	5	4	12	200	12000	400	1000
ADO3340PA	24.4	100	330	24	11	4	16	200	4000	400	250
ADO5022PA	32.4	330	330	32	6.9	4	24	200	7200	400	350
ADS5022PA	32.4	330	330	32	6.9	4	24	200	7200	400	350
ADO7032A	16.4	60	330	16	3.4	4	12	200	20400	400	1700
ADS127A	24.4	100	330	24	7.9	4	16	200	7200	400	450
ADS125A	24.4	100	330	24	6.1	4	16	200	10400	400	650
ADO43A	16.4	60	330	16	3.4	4	8	200	19200	400	2000
ADO54A	16.4	60	330	16	4.7	4	12	200	14400	400	1200
ADO75A	16.4	60	330	16	5.4	4	12	200	12000	400	1000
ADO105A	16.4	60	330	16	5.8	4	12	200	12000	400	1000
ADTISM-4	16.4	330	330	16	3.2	4	8	200	12000	400	2700
ADTISM-3	12.4	330	330	12	2.4	4	8	200	24000	400	3000
ADDLCSM-507I	24.4	100	330	24	5.9	4	12	200	12000	400	1500
ADDLCSM-581I	24.4	100	330	24	5.9	4	12	200	12000	400	900

INDUCTORS

179