




FEATURES

- ※ Low profile 1.6mm height
- ※ Gold contact for high reliability
- ※ Top tape type for washing process


APPLICATION

- ※ Industrial control
- ※ Automatic machines control
- ※ NB, electronic devices

SPECIFICATION

Contact Rating	25mA, 24V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	300V AC/1 minute
Operating Force	500gf max.
Travel	0.6mm
Operating Life	1,000 cycles
Operating Temp.	-40°C ~ +85°C
Storage Temp.	-40°C ~ +85°C

CIRCUIT



PACKAGE


<Tube>

DHN(F)-02(-T): 125 pcs
DHN(F)-04(-T): 75 pcs
DHN(F)-06(-T): 54 pcs
DHN(F)-08(-T): 40 pcs
DHN(F)-10(-T): 33 pcs



<Tape & Reel>

DHN: 4000 pcs
DHNF: 2500 pcs



HOW TO ORDER



DHN





P.C.B. LAYOUT





PART NO.	NO.OF POS	DIM A
DHN-02	2	3.77
DHN-04	4	6.31
DHN-06	6	8.85
DHN-08	8	11.39
DHN-10	10	13.93

DHNF



P.C.B. LAYOUT



PART NO.	NO.OF POS	DIM A
DHNF-02	2	3.77
DHNF-04	4	6.31
DHNF-06	6	8.85
DHNF-08	8	11.39
DHNF-10	10	13.93