

Base strip - MSTBVA 2,5/ 2-G-5,08 - 1755736

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 2, Pitch: 5.08 mm, Color: green, Contact surface: Tin, Mounting: Soldering



The figure shows a 10-position version of the product

Product Features

- Plug-in direction vertical to the PCB
- ✓ Versions with side panel
- For soldering onto the PCB

Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|-----------------|
| Minimum order quantity | 250 pc |
| GTIN | 4 017918 029319 |
| Weight per Piece (excluding packing) | 0.88 g |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Dimensions

| Length | 8.6 mm |
|--------------------------|----------|
| Pitch | 5.08 mm |
| Dimension a | 5.08 mm |
| Width | 12.16 mm |
| Constructional height | 12 mm |
| Height | 15.9 mm |
| Length of the solder pin | 3.9 mm |
| Pin dimensions | 1 x 1 mm |



Base strip - MSTBVA 2,5/ 2-G-5,08 - 1755736

Technical data

Dimensions

| Hole diameter 1.4 mm |
|----------------------|
|----------------------|

General

| Range of articles | MSTBVA 2,5/G |
|--|--------------|
| Insulating material group | I |
| Rated surge voltage (III/3) | 4 kV |
| Rated surge voltage (III/2) | 4 kV |
| Rated surge voltage (II/2) | 4 kV |
| Rated voltage (III/3) | 250 V |
| Rated voltage (III/2) | 320 V |
| Rated voltage (II/2) | 630 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 12 A |
| Maximum load current | 12 A |
| Insulating material | PA |
| Flammability rating according to UL 94 | V0 |
| Color | green |
| Number of positions | 2 |

Classifications

eCl@ss

| eCl@ss 4.0 | 272607xx |
|------------|----------|
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

ETIM

| ETIM 3.0 | EC001121 |
|----------|----------|
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

UNSPSC

| UNSPSC 6.01 | 30211810 |
|---------------|----------|
| UNSPSC 7.0901 | 39121409 |



Base strip - MSTBVA 2,5/ 2-G-5,08 - 1755736

Classifications

UNSPSC

| UNSPSC 11 | 39121409 |
|--------------|----------|
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Phoenix Contact 2015 @ - all rights reserved http://www.phoenixcontact.com