



ATLAS WIRE CORPORATION

VINYL LEAD AND HOOKUP WIRE 1/32" WALL, 600 VOLTS

STYLE	1011	80c	VW-1	CSA TR-32 90c
	1013	90c	VW-1	CSA TEW 105c
	1015	105c	VW-1	CSA AWM 90c OR 105c
	1032	90c	VW-1 - 1000 VOLT	
	1230	105c	VW-1 - MOISTURE RESISTANT 60c	



Recognized under the Component Program of Underwriters Laboratories Inc.

**CONDUCTORS: SOLID, BARE STRANDED, TINNED STRANDED,
HEAVY TINNED STRANDED, TOPCOAT, PREBOND, OVERCOAT**

ATLAS PART NO.	AWG	CONDUCTOR*	COND DIAM		OD		APPROX LBS./M FT.	STD PUT-UP
			IN	MM	IN	MM		
2607T1015	26	7/34	0.019	0.483	0.081	2.057	3.81	10 M/FT
2401T1015	24	SOLID	0.020	0.508	0.083	2.108	4.22	10 M/FT
2407T1015	24	7/32	0.024	0.610	0.086	2.184	4.60	10 M/FT
2201T1015	22	SOLID	0.025	0.635	0.088	2.235	5.27	5 M/FT
2207T1015	22	7/30	0.030	0.762	0.092	2.337	5.75	5 M/FT
2001T1015	20	SOLID	0.032	0.810	0.094	2.388	6.78	5 M/FT
2010T1015	20	10/30	0.038	0.966	0.100	2.540	7.18	5 M/FT
1801T1015	18	SOLID	0.040	1.016	0.103	2.616	9.10	5 M/FT
1816T1015	18	16/30	0.048	1.219	0.110	2.794	9.59	5 M/FT
1601T1015	16	SOLID	0.051	1.295	0.113	2.870	12.67	5 M/FT
1626T1015	16	26/30	0.059	1.500	0.121	3.073	13.33	5 M/FT
1401T1015	14	SOLID	0.064	1.626	0.127	3.226	18.07	2.5 M/FT
1441T1015	14	41/30	0.075	1.905	0.137	3.480	18.96	2.5 M/FT
1201T1015	12	SOLID	0.081	2.057	0.144	3.658	26.51	2.5 M/FT
1265T1015	12	65/30	0.095	2.410	0.157	3.988	27.83	2.5 M/FT
1001T1015	10	SOLID	0.102	2.591	0.164	4.166	39.47	2 M/FT
1005T1015	10	105/30	0.115	2.920	0.177	4.496	41.10	2 M/FT

* AVAILABLE IN ALTERNATE STRANDINGS

UL FILE NO. E-25635
CSA FILE NO. TR-32 LL17450
TEW LL29012
AWM LL38335

www.atlaswirecorp.com