



Dimensions (mm)

L	L ₁	W	T	d	F
7.5±0.5	35±2	8.3±0.5	3.4±0.2	Φ1.05±0.05	5.2±0.5

Key Features

- Plastic Case
- Non-resettable
- High Accuracy of Function Temp.
- High Surge Capacity
- RoHS & REACH Compliant

Specifications

Model	T_f	Fusing Temp.	T_h	T_m	I_r	U_r	I_n 8/20 μ s (15 Times)	I_{max} 8/20 μ s (1 Time)	UL [®]	CUL [®]	VDE [®]	CCC [®]	PSE [®]	RoHS	REACH
	(°C)	(°C)	(°C)	(°C)	(A)	(Vac)	(kA)	(kA)	UL	CUL	VDE	CCC	PSE		
T102	102	98±2	72	200	15 / 16	250	6	12	●	●	●	●	●	●	●
T115	115	111±2	85	200	15 / 16	250	6	12	●	●	●	●	●	●	●
T136	136	131±2	106	200	15 / 16	250	6	12	●	●	●	●	●	●	●
T150	150	145±2	118	200	15 / 16	250	6	12	●	●					●

Applications

- SPD
- Power Strips
- Lamps
- Switched-mode Power Supply
- Home Electrical Appliances
- Batteries

Customization

- Other Temp. Can be Customized
- The Length of Lead Wires Can be Customized as Required.
- Lead Wires Can be Insulated

Packaging Information

- Q'TY:
20 kPCS/Carton
- Carton Size:
440 × 300 × 260 (mm)

Agency Information

- CCC: 2009010205346078
- UL / CUL: E214712
- VDE: 40018082
- PSE: 09020121/45/46